

Market Data Technical Specification v4.2 [Pre-Release]

May 2026



Table of Contents

Version History.....	4
1 Introduction.....	6
1.1 Connectivity.....	6
1.2 Enquiries / Support.....	6
2 Service Description.....	7
2.1 Real Time Market Data Feed.....	7
2.2 Snapshot Feed.....	8
2.3 Replay Service.....	9
2.4 Statistical Inclusion.....	9
3 Market Data Message Formats.....	10
3.1 Data Types.....	10
3.2 Multicast Packet Structure.....	10
3.3 Message Header and Heartbeat.....	11
3.3.1 Message Header.....	11
3.3.2 Heartbeat Message.....	11
3.4 Continuous Data Feed Messages.....	11
3.4.1 MD Bundle Start Message.....	11
3.4.2 MD Bundle End Message.....	11
3.4.3 Order Add Message.....	12
3.4.4 Order Cancel Message.....	12
3.4.5 Order Modify Message.....	12
3.4.6 Trade Message.....	13
3.4.7 Trade Bust Message.....	14
3.4.8 Tick Table Data Message.....	14
3.4.9 Security Definition Message.....	15
3.4.10 Security Status Message.....	16
3.5 Auction On Demand (AoD) Data Feed Messages.....	17
3.5.1 AoD Update Message.....	17
3.5.2 AoD Security Status Message.....	18
3.5.3 AoD Trade Message.....	18
3.5.4 AoD Trade Bust Message.....	18

3.6	Market at Close (MaC) Data Feed Messages	18
3.6.1	MaC Update Message	18
3.6.2	MaC Trade Message	18
3.6.3	MaC Trade Bust Message	18
3.6.4	MaC Security Status Message	18
3.7	Snapshot Feed Messages	19
3.7.1	Snapshot Start Message.....	19
3.7.2	Book Status Message	19
3.7.3	Book Entry Message.....	19
3.7.4	MaC Book Entry Message	20
3.8	Replay Service Messages	20
3.8.1	Login Message	20
3.8.2	Replay Request Message	21
3.8.3	Replay Response Message	21
3.9	Flags	22
3.9.1	MMT Flags.....	22
3.9.2	MdFlags.....	23

Version History

Version	Date	Comments
1.0	24 Jun 2013	Initial version
1.1	12 Jul 2013	Update to Security Status message; Addition of Snapshot Feed messages; Addition of Replay Service messages
1.2	31 Mar 2014	Addition of Market at Close (MaC)
1.2.1	01 Apr 2014	Addition of Closing Market messages
1.2.2	02 Apr 2014	Update to Market Flags in the Security Status message; Addition of MaC Update message, Update to Indicative Price in the Book Status message
1.2.3	11 Jun 2014	Update to MaC Update message
1.2.4	05 Dec 2014	Update to when Security Definition messages may be sent (during the day if there are changes or corrections)
1.2.5	30 Mar 2015	Clarification of tradeType differences for Trade messages
2.0	20 Nov 2017	Addition of MiFID II feed – new Trade message which includes binary MMT flags
2.1	16 Apr 2018	Addition of trade types – LIS and Benchmark Cross; Removal of non-MMT feeds; Addition of Market at Close (MaC) feeds
2.2	25 Apr 2018	Addition of Auction on Demand (AoD) trade type
2.3	16 Apr 2019	Addition of MaC Book Entry Message
2.3.1	08 May 2019	Update to 'Real Time Market Data Feed'
2.4	15 Mar 2021	Addition of <i>flags</i> in Security Definition message Correction of AoD Update Message behaviour
2.4.1	07 Jun 2021	Update to <i>flags</i> in Security Definition message Updated representation of <i>marketFlags</i> in Security Status message
2.4.2	11 Apr 2022	Update to Security Status message <i>marketFlags</i> and <i>tradingStatus</i> Addition of Trading Status section Update to MaC Book Entry message to correct order price
2.4.2.1	27 Apr 2022	Update to Security Status message to <i>marketFlags (Bit 4)</i> Removal of integer representation of <i>marketFlags</i> . Subscribers should use the bit representation
2.4.3	14 Mar 2023	Correction of datatypes in Security Definition message <i>indicativePrice</i> and <i>matchVol</i> now return 0 when AoD has uncrossed
2.5	Sept 2023	Addition of <i>mdFlags</i> on Order Add, Order Modify, Order Cancel and Trade message Addition of Flags section
4.0	March 2025	Addition of <i>exchangeSymbol</i> and Aquis VWAP Match (AVM) functionality to Security Definition message. Addition of lot sizes and decimal places for <i>lotSizes</i>
4.1	October 2025	Addition of Segment MIC to Trade Message Addition of information on statistical inclusion
4.2	May 2026	Addition of Bundle Start and Bundle End Messages

Version	Date	Comments
		Addition of Publication Timestamp Addition of Timestamp and MarketId to Security Definition Message

1 Introduction

Aquis Exchange (Aquis) provides its MTF market data to trading Members and market data vendors via a number of IP multicast feeds. These feeds consist of real-time order and trade feeds publishing continuously throughout the trading day and snapshot feeds publishing order book data at regular intervals. Additionally, message replay servers are available to offer message gap recovery if required.

This document describes the protocol and message formats for these market data feeds.

1.1 Connectivity

Aquis offers both WAN-shaped and Gig-shaped versions of the market data feed for recipients to use depending on the nature of their connectivity to the Aquis data centres. Furthermore, Aquis offers more than one channel for receiving the market data (for example, two channels from the primary data centre for a particular data stream and a further channel for this stream from the secondary data centre).

The current details of the network configuration, multicast address information and login credentials for the replay service, for both production and test feeds, can be provided by the Aquis connectivity team.

1.2 Enquiries / Support

Please contact the Aquis support team at support@aquis.eu for any questions relating to this document.

2 Service Description

2.1 Real Time Market Data Feed

The Aquis market data servers monitor trading activity on the system and convert these events into market data messages.

This data is anonymised, so that the messages do not include any information identifying the trading Members involved.

Continuous order and trade market data is published using the following messages:

- **Order Add**
- **Order Modify**
- **Order Cancel**
- **Trade Report**
- **Trade Bust**

Auction on Demand (AoD) phases are published with a separate message:

- **AoD Update**

The Market at Close (MaC) phase introduces a new message, purely for the purpose of the MaC, published on MaC Data Feeds:

- **MaC Update**

Order and Trade reference numbers are assigned by Aquis and are unique for the day. Note that a particular order reference can appear multiple times on the market data stream and always represents the same order within the trading system.

The security identifier on the market data messages is a numeric value. Aquis provides a security reference data file for recipients to interpret this security ID, giving information such as Uniform MTF code, ISIN, currency and MIC for the security. Another reference data file is provided defining the tick tables that apply to the securities. These reference data files are made available for download pre-market open and will be updated daily to reflect securities admitted to or removed from trading and any relevant corporate actions.

Reference data to identify the securities traded on Aquis and to provide tick table information is also published on the feed at the start of the day, before market open, using the following messages:

- **Tick Table Data**

- **Security Definition**

Note that rarely a **Security Definition** may be published during the trading day if changes or corrections to the data are necessary.

As the trading status of a security changes, either due to market opening or closing or due to Aquis applying a trading halt or regulatory suspension, this update is published using a **Security Status** message.

Each of these messages on a particular feed carries a sequence number for the day's trading session. The first message of the day is sequence number 1, and this value is incremented with each message published on the data feed.

During trading hours, a **Heartbeat** message is sent if no trading data has been published for a period of one second. The Heartbeat message carries the sequence number of the next expected trading data message, and so can be used to detect gaps in periods of low trading activity. It does not itself cause the sequence number of the data stream to be incremented. Heartbeat messages are also sent during periods of technical connectivity pre and post market hours to help recipients check their multicast connectivity.

2.2 Snapshot Feed

In addition to the continuous real-time feed, an order book snapshot is published at fixed intervals (10 seconds) on a separate feed, providing the full book depth of each traded security.

There is a snapshot feed corresponding to each of the market-split continuous feeds. The first message of each snapshot publication is a **Snapshot Start** message, identifying the sequence number in the continuous stream at the time this snapshot was captured.

For each of these securities, a **Book Status** message is published reporting the status of the security and identifying the number of open orders in that security followed by a series of **Book Entry** messages for each of these orders. If there are currently no open orders for a particular security, then the Book Status message carries an *entries* value of 0 (zero) and there will be no Book Entry messages.

The snapshot feed may be used together with the continuous feed as a way to establish and then maintain a view of the Aquis order book as a starting point for a recipient who has missed the market open and connects during the trading day. The snapshot may be used similarly to recover from an outage and to reconstruct the state of the book on re-connecting to the market data feed.

The snapshot data may also be used by a recipient to verify that they are correctly processing the continuous feed to construct an accurate representation of the order book.

2.3 Replay Service

To allow recipients to recover specific messages that may have been missed from the continuous feed, Aquis offers a TCP/IP replay service for each feed. This service is provided over TCP/IP and recipients wishing to use it should contact Aquis to request login credentials. On connecting to a replay server, the recipient should send a **Login** message. The server will send back a **Replay Response** indicating acceptance, or else will drop the connection if not authenticated. A connection to a replay server can either be maintained from the beginning of the day or opened as needed.

To recover missed messages, the recipient should send a **Replay Request** message. The replay server validates the request and will respond with the requested range of market data messages. If the request cannot be serviced then a **Replay Response** will be sent to explain the failure of the request.

2.4 Statistical Inclusion

The table below outlines whether the following trade types should be included in the calculation of key market statistics:

- **High/Low**
- **Open/Close**
- **Total Volume**
- **Total Value Traded**

	MIC (UK / EU)	High/Low	Open/Close	Total Volume	Total Value Traded
CLOB	AQXE / AQEU	Yes	Yes	Yes	Yes
AMP	AQXD / AQED	Yes	No	Yes	Yes
AoD	AQXA / AQEA	Yes	No	Yes	Yes
Market at Close (MaC)	(Same as CLOB)	Yes	Yes	Yes	Yes
LIS Cross	(Same as CLOB)	No	No	Yes	Yes
Benchmark Cross	(Same as CLOB)	No	No	Yes	Yes
AVM	AVXE / AVEU	No	No	Yes	Yes

3 Market Data Message Formats

This section provides details of the message formats used within the Aquis market data feeds. This includes data types, multicast packet header, message header and message fields and descriptions.

3.1 Data Types

In all messages, 1-byte packing is used and all integers are represented in little-endian format.

Data Type	Size	Value
u8	1	unsigned integer 0 – 255
u16	2	unsigned integer 0 – 65,535
u32	4	unsigned integer 0 – 4,294,967,295
u64	8	unsigned integer 0 – $2^{64} - 1$
char(<i>n</i>)	<i>n</i>	Left justified ascii string, padded with zero (0x00) to length <i>n</i>
price	8	unsigned integer representing price with 5 decimal places implied e.g. value 1462500 represents a price of 14.625
timestamp	8	unsigned integer representing elapsed time in nanoseconds* since Unix epoch 00:00 UTC on 1 st January 1970

*The Aquis system is accurate to the nearest μ s. This time is multiplied by 1000 to convert μ s to ns.

3.2 Multicast Packet Structure

Each packet on the multicast feeds may carry more than one market data message. The structure is as follows:

- **Packet Header** u8 field message count – number of messages (*n*) in this packet
- **Message 1**
- **Message 2**
- ...
- **Message n**

The sequence number of each message in the feed is carried in the header of the individual market data messages.

The packet header ‘message count’ and the sequence number of the first message in the packet can be used together to check for dropped packets by recipients of the multicast data streams.

Note that if the packet is carrying a Heartbeat message then the next expected sequence number should not be incremented.

3.3 Message Header and Heartbeat

3.3.1 Message Header

All market data messages carry a standard message header, as follows:

Field Name	Type	Offset	Width	Description
msgType	u8	0	1	Message type identifier
length	u8	1	1	Length of market data message, including header
seqNo	u32	2	4	Sequence number of this message in the market data stream for the current trading day

3.3.2 Heartbeat Message

The Heartbeat message carries no data; it is simply a message header with *msgType* of 1. As the message carries no business data it does not affect stream sequence number. The *seqNo* field carries the sequence number of the next business data message expected on the multicast stream.

3.4 Continuous Data Feed Messages

3.4.1 MD Bundle Start Message

The bundle start and end messages are published when a group of messages is generated within the same sequencer cycle. MD Bundle Start is sent at the beginning of the cycle, before any associated messages are published.

Field Name	Type	Offset	Width	Description
<i>Header</i>		0	6	<i>msgType = 34</i>

3.4.2 MD Bundle End Message

Md Bundle End is sent at the conclusion of the bundle to indicate that all messages generated during the sequencer cycle have now been published.

Field Name	Type	Offset	Width	Description
<i>Header</i>		0	6	<i>msgType = 35</i>

3.4.3 Order Add Message

The Order Add message is published when order quantity is posted to the order book for a particular security:

Field Name	Type	Offset	Width	Description
<i>Header</i>		0	6	<i>msgType = 2</i>
securityID	u16	6	2	Numeric identifier of the relevant security
side	u8	8	1	1 = Buy Order, 2 = Sell Order
quantity	u32	9	4	Number of shares being added to the book
price	u64	13	8	The price of the order
orderRef	u32	21	4	Unique order reference number for the day
timestamp	u64	25	8	Timestamp of this market data event
mdFlags	u8	33	1	Refer to mdFlags for values
pubTimestamp	u64	34	8	Timestamp that the market data event was published

3.4.4 Order Cancel Message

The Order Cancel message is published when a visible order is removed from the book. The order may have been cancelled by the trading Member or by the Aquis support team, the market may have closed, or the order's time-in-force may have expired.

Field Name	Type	Offset	Width	Description
<i>Header</i>		0	6	<i>msgType = 3</i>
securityID	u16	6	2	Numeric identifier of the relevant security
orderRef	u32	8	4	Unique order reference number for the day
timestamp	u64	12	8	Timestamp of this market data event
mdFlags	u8	20	1	Refer to mdFlags for values
pubTimestamp	u64	21	8	Timestamp that the market data event was published

3.4.5 Order Modify Message

The Order Modify message is published when a visible order is modified by the client (change of price and/or quantity). The order reference number remains the same on order modification.

Note that on revision of quantity down the order retains its position in the book, otherwise the book is re-ordered.

Field Name	Type	Offset	Width	Description
<i>Header</i>		0	6	<i>msgType = 4</i>
securityID	u16	6	2	Numeric identifier of the relevant security
quantity	u32	8	4	Number of shares remaining in the book
price	u64	12	8	The price of the order
orderRef	u32	20	4	Unique order reference number for the day
timestamp	u64	24	8	Timestamp of this market data event
mdFlags	u8	32	1	Refer to mdFlags for values
pubTimestamp	u64	33	8	Timestamp that the market data event was published

3.4.6 Trade Message

Whenever an order trades, partially or fully, a Trade message is published.

Field Name	Type	Offset	Width	Description
<i>Header</i>		0	6	<i>msgType = 5</i>
securityID	u16	6	2	Numeric identifier of the relevant security
tradeType	u8	8	1	Code identifying type of trade (see below)
quantity	u32	9	4	Number of shares traded
price	u64	13	8	The execution price
orderRef	u32	21	4	Unique order reference number for the day, for <i>tradeType</i> 1 (visible), zero if against hidden quantity or a MaC trade
tradeRef	u32	25	4	Trade reference number
timestamp	u64	29	8	Timestamp of this market data event
MIC	char(4)	37	4	Segment MIC
Binary MMT	u32	41	4	Post-trade regulatory flags (MMT) Please see MMT flags
mdFlags	u8	45	1	Refer to mdFlags for values
pubTimestamp	u64	46	8	Timestamp that the market data event was published

The *tradeType* field is used to identify the category of this trade. Currently assigned codes are as follows, others may be added to correspond to new services or order types:

- 1 = a trade against visible order quantity in the continuous trading order book
- 2 = a trade against hidden or reserve quantity in the continuous trading order book
- 3 = Market at Close (MaC) trade
- 4 = LIS Cross trade
- 5 = Benchmark Cross trade
- 6 = Auction on Demand (AoD) trade
- 12 = Aquis VWAP Match (AVM) trade

For a trade against visible order quantity, the traded quantity should be removed from the associated order in the order book. If the order has fully traded then it should be removed from the order book.

Note that if an incoming aggressive order trades against both the visible peak and hidden reserve portions of an iceberg order, this will result in two Trade messages on the feed. The first, for the visible portion, will carry *tradeType* 1 with an associated *orderRef* for the peak. The second, for the reserve portion, will carry *tradeType* 2 and *orderRef* zero as this reserve order quantity was not previously published to the feed. When the iceberg order is refreshed with a new peak, this will be published as an Order Add message with a new *orderRef* value.

3.4.7 Trade Bust Message

If a trade has been declared erroneous by Aquis then a Trade Bust message is published.

Field Name	Type	Offset	Width	Description
<i>Header</i>		0	6	<i>msgType</i> = 6
securityID	u16	6	2	Numeric identifier of the relevant security
quantity	u32	8	4	Number of shares of the original trade
price	u64	12	8	The execution price of the original trade
tradeRef	u32	20	4	Trade reference of the busted trade
timestamp	u64	24	8	Timestamp of this market data event
Binary MMT	u32	32	4	Post-trade regulatory flags (MMT) Please see MMT flags
pubTimestamp	u64	36	8	Timestamp that the market data event was published

3.4.8 Tick Table Data Message

A series of Tick Table Data messages are published pre-market to specify the dynamic tick tables and static ticks that apply to the securities traded on Aquis. This data controls the valid price increments at which orders may be entered onto the Aquis order book.

For dynamic tick tables, there are a set of messages carrying the id and name of the table; these define the tick size (price increment) that applies at increasing price levels. For static ticks there is a single message.

Field Name	Type	Offset	Width	Description
Header		0	6	<i>msgType = 7</i>
tickTableID	u8	6	1	Numeric identifier for this tick table or static tick
name	char(10)	7	10	Short name
threshold	u64	17	8	The price threshold at which this tick data applies
tickSize	u64	25	8	The tick size (price increment)

3.4.9 Security Definition Message

A series of Security Definition messages are published pre-market to identify the securities traded on Aquis (those relevant to the particular feed e.g. Euronext securities). These messages allow the *securityId* field to be used on later trading related market data messages to associate with a particular security in the recipient's system. Note that this message may be sent during the day if a change or correction is necessary for a particular security.

Field Name	Type	Offset	Width	Description	
Header		0	6	<i>msgType = 8</i>	
securityID	u16	6	2	Numeric identifier of the relevant security	
UMTF	char(6)	8	6	Uniform UMTF code for the security	
ISIN	char(12)	14	12	ISIN for the security	
currency	char(3)	26	3	Trading currency for the security	
MIC	char(4)	29	4	MIC for the security's market of listing	
tickTableId	u8	33	1	Numeric identifier for this security's tick table	
flags	u16	34	2	Bit 0 – macEnabled	0 = Security is not enabled for the MaC 1 = Security is enabled for the MaC
				Bit 1 – testStock	0 = Security is not a test stock 1 = Security is a test stock
				Bit 2 – illiquid	0 = Security is liquid 1 = Security is illiquid
				Bit 3	<i>Reserved</i>
				Bit 4 – aodEnabled	0 = Security is not enabled for the AoD

Field Name	Type	Offset	Width	Description
				1 = Security is enabled for the AoD
				Bits 5-6 <i>Reserved</i>
				Bit 7 – avxEnabled 0 = Security is not enabled for AVM 1 = Security is enabled for AVM
				Bit 8 – 15 <i>Reserved</i>
exchangeSymbol	char(20)	36	20	Exchange symbol for the security
lotSize	u64	56	8	Lot size for the security. This will always be set to 1,000,000,000 to represent a lot size of 1
lotSizeDecimal	u8	64	1	Number of decimals implied in lotSize Will always be set to 9
timestamp	u64	65	8	Timestamp of this market data event
marketId	u16	73	2	Numerical market identifier for the security

3.4.10 Security Status Message

The Security Status message is published when the trading status of a security changes or when there is a change to the status of the market on Aquis to which the security belongs.

Field Name	Type	Offset	Width	Description
<i>Header</i>		0	6	<i>msgType = 9</i>
securityID	u16	6	2	Numeric identifier of the relevant security
tradingStatus	u8	8	1	Possible values: 1 = Active 2 = Halted 3 = Suspended 8 = AoD Start 24 = AoD Finish See notes below
marketFlags	u8	9	1	Bit 0 – trading 0 = Continuous Trading Closed 1 = Continuous Trading Open
				Bit 1 – macOpen 0 = MaC is Closed 1 = MaC is Open
				Bit 2 – macRun 0 = MaC is not locked down 1 = MaC is locked down
				Bit 3-7 <i>Reserved</i>
timestamp	u64	10	8	Timestamp of this market data event

Field Name	Type	Offset	Width	Description
tradingPhase	u8	18	1	Possible values: 0 = Closed 1 = Continuous
pubTimestamp	u64	19	8	Timestamp that the market data event was published

3.4.10.1 Trading Status

If a security's *tradingStatus* is 'halted' (by Aquis support for internal reasons) or 'suspended' (for regulatory reasons) then the security cannot be traded. Auctions that are running during a halt or suspension will be cancelled.

If a security's *tradingStatus* is 'active', orders for this security can only be entered if the market for this security on Aquis is open.

If a security's *tradingStatus* is 'AoD start', this signals that an AoD order has entered an empty order book and triggered the AoD auction process for this security. These statuses will only apply to Aquis Europe.

If a security's *tradingStatus* is 'AoD end', this signals that the auction order book has emptied for this security. These statuses will only apply to Aquis Europe.

3.5 Auction On Demand (AoD) Data Feed Messages

AoD is available during the hours of continuous trading.

3.5.1 AoD Update Message

During the AoD this message is used to publish the indicative price and indicative matched volume.

An indicativePrice and matchVol of 0 indicates that an auction has just uncrossed.

Field Name	Type	Offset	Width	Description
<i>Header</i>		0	6	<i>msgType = 17</i>
securityID	u16	6	2	Numeric identifier of the relevant security
indicativePrice	u64	8	8	Indicative auction price
matchVol	u32	16	4	Indicative matched volume
timestamp	u64	20	8	Timestamp of this market data event

pubTimestamp	u64	28	8	Timestamp that the market data event was published
--------------	-----	----	---	--

3.5.2 AoD Security Status Message

As provided in Section 3.4.8.1

3.5.3 AoD Trade Message

As provided in Section 3.4.4.

3.5.4 AoD Trade Bust Message

As provided in Section 3.4.5.

3.6 Market at Close (MaC) Data Feed Messages

3.6.1 MaC Update Message

During the MaC this message is used to publish the indicative price from the buy and sell order totals.

Field Name	Type	Offset	Width	Description
<i>Header</i>		0	6	<i>msgType = 16</i>
securityID	u16	6	2	Numeric identifier of the relevant security
indicativePrice	u64	8	8	Indicative auction price
closingBuyQty	u32	16	4	Total order quantity on the buy side during the closing market, otherwise set to 0
closingSellQty	u32	20	4	Total order quantity on the sell side during the closing market, otherwise set to 0
timestamp	u64	24	8	Timestamp of this market data event

Note that the matched quantity and unmatched quantity (imbalance) can be determined by comparing the *closingBuyQty* and *closingSellQty* values.

3.6.2 MaC Trade Message

As provided in Section 3.4.4.

3.6.3 MaC Trade Bust Message

As provided in Section 3.4.5.

3.6.4 MaC Security Status Message

As detailed in Section 3.4.8.

3.7 Snapshot Feed Messages

3.7.1 Snapshot Start Message

A Snapshot Start message is published as the first message in a snapshot to identify the sequence number in the continuous stream that this snapshot relates to. It also states the number of securities being reported in this snapshot.

Field Name	Type	Offset	Width	Description
Header		0	6	<i>msgType = 10</i>
streamSeqNo	u32	6	4	The sequence number of the last message in the continuous stream which relates to this snapshot
securityCount	u16	10	2	Number of securities reported in this snapshot
timestamp	u64	12	8	Timestamp of this snapshot

3.7.2 Book Status Message

A Book Status message is published to report the trading and market status of each security and the number of open orders on the order book for the security at the time of the snapshot.

Field Name	Type	Offset	Width	Description
Header		0	6	<i>msgType = 11</i>
securityID	u16	6	2	Numeric identifier security of relevant security
tradingStatus	u8	8	1	See Security Status message
marketFlags	u8	9	1	See Security Status message)
entries	u16	10	2	Number of open orders in the book for this security
closingBuyQty	u32	12	4	Total order quantity on the buy side during the closing market, otherwise set to 0
closingSellQty	u32	16	4	Total order quantity on the sell side during the closing market, otherwise set to 0
indicativePrice	u64	20	8	Indicative auction price

3.7.3 Book Entry Message

An appropriate number of Book Entry messages is published after each Book Status message to provide details of each order and allow the book to be built. Orders are published in price, time priority for one side of the book and then the other.

Field Name	Type	Offset	Width	Description
<i>Header</i>		0	6	<i>msgType = 12</i>
securityID	u16	6	2	Numeric identifier security of relevant security
Side	u8	8	1	1 = Buy Order, 2 = Sell Order
quantity	u32	9	4	Number of open shares
Price	u64	13	8	The price of the order
orderRef	u32	21	4	Unique order reference number for the day

3.7.4 MaC Book Entry Message

During the MaC phase, Aquis will publish the volume of the first 5 valid best bid and offer orders per security in chronological order using the MaC Book Entry Message. This message is a snapshot.

Field Name	Type	Offset	Width	Description
<i>Header</i>		0	6	<i>msgType = 18</i>
securityID	u16	6	2	Numeric identifier security of relevant security
Side	u8	8	1	1 = Buy Order, 2 = Sell Order
Quantity	u32	9	4	Number of open shares
Price	u64	13	8	The price of the order
orderRef	u32	21	4	Unique order reference number for the day

3.8 Replay Service Messages

The replay service allows recipients to recover messages that they have missed from the continuous multicast feed via a dedicated TCP/IP connection, as described in Section 2.3. Note that the *seqNo* field in the standard message header is not relevant for these replay service messages; Aquis will set the field to zero and will ignore the field on messages from data recipients.

3.8.1 Login Message

If a recipient wishes to use the message replay service, they must first be authenticated by sending a Login message to the relevant replay server.

Field Name	Type	Offset	Width	Description
<i>Header</i>		0	6	<i>msgType = 13</i>
username	char(10)	6	10	As assigned by Aquis for the recipient

Field Name	Type	Offset	Width	Description
password	char(10)	16	10	As assigned by Aquis for the recipient

3.8.2 Replay Request Message

The recipient sends a Replay Request message to request a particular message or range of messages from the replay server.

Field Name	Type	Offset	Width	Description
<i>Header</i>		0	6	<i>msgType = 14</i>
beginSeqNo	u32	6	4	Stream seqNo of first message requested
endSeqNo	u32	10	4	Stream seqNo of last message requested

3.8.3 Replay Response Message

Aquis will send a Replay Response message to the recipient to acknowledge a successful Login or to report problems with a Resend Request.

If a Login does not match a valid username or password then the connection is dropped without a response.

If a Resend Request is accepted, Aquis will not send a Replay Response message but will simply send the requested messages over the TCP/IP connection to the recipient.

Field Name	Type	Offset	Width	Description
<i>Header</i>		0	6	<i>msgType = 15</i>
responseCode	u8	6	1	Possible values are: 0 = Login successful 1 = Bad <i>beginSeqNo</i> in Resend Request 2 = Bad <i>endSeqNo</i> in Resend Request

3.9 Flags

3.9.1 MMT Flags

The following table details the supported fields and values for the *Binary MMT* flags.

Field Name	Type	Width	Description
Binary MMT	u32	4	Bit 0 - 2 Market Mechanism 1 - Central Limit Order Book 2 - Quote Driven Market 3 - Dark Order Book 4 - Off Book 5 - Periodic Auction 6 - RFQ 7 - Other
			Bit 3 - 6 Trading Mode 1 - Undefined Auction 2 - Opening Auction 3 - Closing Auction 4 - Intraday Auction 5 - Unscheduled Auction 6 - Continuous Trading 7 - At Market Close 8 - Out of Main Session 9 - On-Exchange Trade Reporting A - Off-exchange Trade Reporting B - Systematic Internalizer Trade Reporting
			Bit 7 - 9 Transaction Category 1 - Dark trade 2 - Trade that has Received Price Improvement 3 - Package Trade 4 - Exchange for Physicals 5 - None Apply
			Bit 10 - 12 Negotiation Indicator or Pre-Trade Transparency Waiver 0 - Negotiated Trade 1 - Negotiated Trade in Liquid Instruments 2 - Negotiated Trade in Illiquid Instruments 3 - Negotiated Trade Other Than Current Market Price 4 - No Negotiated trade 5 - SI Illiquid Instruments

Field Name	Type	Width	Description
			6 - SI Above Standard Market Size 7 - ILQD and SIZE
			Bit 13 Crossing Trade 0 - No 1 - Yes
			Bit 14 - 15 Modification Indicator 1 - Trade Cancellation 2 - Trade Amendment 3 - New Trade
			Bit 16 - 17 Benchmark/Reference Price Indicator 1 - Benchmark Trade 2 - Reference Price Trade 3 - No Benchmark or Ref Price
			Bit 18 Dividend 0 - No 1 - Yes
			Bit 19 - 20 Off Book Automation 1 - Unspecified 2 - Off-Book Non-Automated 3 - Off-Book Automated
			Bit 21 - 23 Price Formation / Discovery Process 1 - Plain Vanilla 2 - Non-price Forming 3 - Trade Not Contributing to Price Discovery 4 - Price Not Currently Available But Pending
			Bit 24 Algorithmic Indicator 0 - No 1 - Yes
			Bit 25 - 27 Publication Mode – Post- Trade Deferral 1 - Immediate Publication 2 - Non-Immediate Publication 3 - LRGS (Large in Scale) 4 - ILQD (Illiquid Instrument) 5 - SIZE (Size Specific) 6 - ILQD and SIZE 7 - ILQD and LRGS
			Bit 28 Deferral Type 0 - None Apply
			Bit 29 Duplicative Indicator 0 - Unique 1 - Duplicative
			Bit 30 – 31 Spare N/A

3.9.2 MdFlags

The following details the supported fields and values for the *mdFlags* block.

Field Name	Type	Width	Description
mdFlags	u8	1	<i>Bit 0</i> Flag to indicate whether there is unrestricted liquidity available at the top of the book.

Field Name	Type	Width	Description
			0 = Restricted liquidity only 1 = Unrestricted liquidity available Please note: For order messages: Refers to the side indicated in the order. For trade messages: Refers to the passive side of the trade.
			<i>Bit 1- 7</i> <i>Reserved</i>